



## MOTO-GRIP JR.™ INSTRUCTIONS, WARNINGS AND INSPECTION GUIDELINES

### INSTRUCTIONS

1. Thread left end of Moto-Grip Jr. belt through left rear handgrip on Moto-Grip, and connect left end of Moto-Grip Jr. to lower left side of Moto-Grip using side release buckle provided.
2. Put Moto-Grip on like a standard backpack (operator).
3. Mount vehicle (operator and child passenger).
4. With child's assistance, pass right end of Moto-Grip Jr. under child's left arm, behind the back, under right arm, through right rear handgrip on Moto-Grip, and connect right end of Moto-Grip Jr. to lower right side of Moto-Grip using side release buckle provided.
5. With child's assistance, center backrest against child's lower-middle back and adjust length of Moto-Grip Jr. to fit snugly enough for backrest to remain in position without slipping down.
6. Direct child to firmly grip rear left and right Moto-Grip passenger handgrips at all times.

### WARNINGS

- Failure to comply with all Moto-Grip Jr. instructions, warnings and inspection guidelines may result in severe injury or death. If you have any questions or concerns, do not hesitate to contact us at [sales@hatchventures.com](mailto:sales@hatchventures.com) or 212-281-6144.
- Motorcycling, mopeding, ATV riding and snowmobiling are inherently risky. The Moto-Grip Jr. does not eliminate the risk of accidental passenger ejection, serious injury or death. Therefore, always drive safely and responsibly, especially when carrying a passenger.
- The Moto-Grip Jr. is not a substitute for safety lessons or any other safety equipment, including helmet, eye protection, padding, and proper outerwear.
- Under no circumstances should a child be permitted to ride on a motorcycle, moped, ATV or snowmobile until mature enough to understand and follow directions from a qualified adult.
- The Moto-Grip Jr. is not intended for any use other than facilitating motorcycle, moped, ATV and snowmobile passenger safety, as delineated in the product description, instructions, warnings, and inspection guidelines.
- Inspect Moto-Grip Jr. before each use (**see Inspection Guidelines below**).
- Do not use Moto-Grip Jr. if hardware is damaged or webbing is cut, frayed, burnt, melted or abraded.
- Protect product from chemical, environmental & mechanical damage when stored.
- Prior to operating vehicle, check that the Moto-Grip Jr. is securely fastened to the Moto-Grip and positioned snugly around child's lower-middle back, under child's arms.
- If child's position on seat shifts significantly while operating the vehicle, do not divert eyes from road or remove hands from handle bar while vehicle is moving. Employ turn signal, break evenly, pull over to roadside, and bring vehicle to a complete stop at a safe distance from moving traffic.
- Never exceed the Moto-Grip Jr.'s **Child Passenger Weight Limit: 300 LBS/136 KGS.**

### INSPECTION GUIDELINES

The entire product must be visually inspected before each use and it shall be removed from service if any of the following are detected:

- Holes, tears, cuts, snags or embedded material.
- Broken or worn stitches where the hardware is sewn to child safety strap.
- Acid or alkali burns.
- Melting, charring, or weld spatters on any part of the webbing.
- Excessive abrasive wear or crushed webbing.
- Signs of ultraviolet (UV) light degradation.
- Distortion, excessive pitting, corrosion, or other damage to hardware or end fittings.
- Any conditions which cause doubt as to the strength of the product.

Even damage that looks minor can significantly degrade the strength of the product. If you have any doubts about the condition of the product, **DO NOT USE IT.** Moreover, never attempt to perform temporary field repairs on this product.