



## MOTO-GRIP™ INSTRUCTIONS, WARNINGS AND INSPECTION GUIDELINES

### INSTRUCTIONS

1. Put Moto-Grip on like a standard backpack.
2. Position rear cross straps against mid-upper back.
3. Connect lower sternum strap on front of harness.
4. Adjust shoulder straps until lower sternum strap is parallel with sternum.
5. Tighten lower sternum strap and shoulder straps until harness is snug against the body.
6. Connect upper chest strap on front of harness and tighten until snug against the chest.
7. After adjusting for proper fit, secure excess material on all straps using lashes provided.

### WARNINGS

- Failure to comply with all Moto-Grip instructions, warnings and inspection guidelines may result in severe injury or death. If you have any questions or concerns, do not hesitate to contact us at [sales@hatchventures.com](mailto:sales@hatchventures.com) or 212-281-6144.
- Motorcycling, mopeding, ATV riding and snowmobiling are inherently risky. The Moto-Grip does not eliminate the risk of accidental passenger ejection, serious injury or death. Therefore, always drive safely and responsibly, especially when carrying a passenger.
- The Moto-Grip is not a substitute for safety lessons or any other safety equipment, including helmet, eye protection, padding, and proper outerwear.
- Under no circumstances should a passenger under the age of 12 be permitted to ride on the back of a motorcycle, moped, ATV or snowmobile without use of both the Moto-Grip and Moto-Grip Jr..
- The Moto-Grip is not intended for any use other than facilitating motorcycle, moped, ATV, and snowmobile passenger safety, as delineated in the product description, instructions, warnings, and inspection guidelines.
- Inspect Moto-Grip before each use (**see Inspection Guidelines below**).
- Do not use Moto-Grip if hardware is damaged or webbing is cut, frayed, burnt, melted or abraded.
- Protect product from chemical, environmental & mechanical damage when stored.
- Check that the Moto-Grip chest strap and sternum strap side release buckles are properly and securely fastened prior to operating the vehicle with a passenger.
- Never exceed the Moto-Grip's **Maximum Passenger Weight Limit: 300 LBS/136 KGS.**

### INSPECTION GUIDELINES

The entire product must be visually inspected before each use and it shall be removed from service if any of the following are detected:

- Holes, tears, cuts, snags or embedded material.
- Broken or worn stitches where the hardware is sewn to harness.
- Acid or alkali burns.
- Melting, charring, or weld spatters on any part of the webbing.
- Excessive abrasive wear or crushed webbing.
- Signs of ultraviolet (UV) light degradation.
- Distortion, excessive pitting, corrosion, or other damage to hardware or end fittings.
- Any conditions which cause doubt as to the strength of the product.

Even damage that looks minor can significantly degrade the strength of the product. If you have any doubts about the condition of the product, **DO NOT USE IT.** Moreover, never attempt to perform temporary field repairs on this product.